



# THE METRO GROUP, INC.

5025 Taconic Blvd. Suite 100  
Long Island City, NY 11106  
Tel: 718-720-7200  
Fax: 718-720-8077

Divisions:  
Metropolitan Rening  
Consolidated Water Conditioning  
Cosmopolitan Chemical  
Petro Con Chemical

## VAPORENE 7515 BIOCIDE FOR COOLING WATER

**Broad-spectrum biocide**  
- controls bacteria, algae

### PRINCIPAL USES

VAPORENE 7515 is a liquid broad-spectrum micro-biocide for control of bacterial, algal and slime deposits commonly found in recirculating cooling water systems, air washers, cooling towers and evaporative condensers.

VAPORENE 7515 helps prevent fouling by penetrating and removing slime deposits from heat transfer surfaces.

**Strong dispersing action**  
- attacks MIC

### DESCRIPTION

VAPORENE 7515 is blended liquid product containing Glutaraldehyde.

**Non-oxidizing treatment**  
- Not corrosive

Appearance	- Clear straw colored liquid
Odor	- Characteristic
Specific Gravity	- 1.03 - 1.05 @ 60°F
Weight per Gallon	- 8.7 lbs.
Solubility	- Miscible in water in all proportions

VAPORENE 7515 is registered with the United States Environmental Protection Agency, Registration No. 10352-23-10778.

**Concentrated**  
- no dilution required

### APPLICATION

VAPORENE 7515 should be fed in shock dosages directly to the cooling tower, evaporative condenser or air washer pan. Dosages for recirculating cooling water systems will depend upon a number of factors; nature and extent of the biological contamination, type and volume being treated, degree of control desired, and retention time in the system. Your local METRO Field Engineer will supply specific dosage instructions.

Heavily contaminated systems should be cleaned prior to treatment, mechanically or with METRO STEROKLEN, a detergent sanitizer. Apply VAPORENE 7515 to the cleaned system or when organic growth is first apparent, as directed.

**Use with VAPORENE**  
cooling water treatments  
complete protection

### HANDLING AND PACKAGING

VAPORENE 7515 is available in 55, 30 and 5 gallon non-returnable, polyethylene drums with 2" opening in head. Do not reuse empty containers.

VAPORENE 7515 is corrosive. Care should be taken in handling, as with all water treatment chemicals. For specific handling instructions, see Material Safety Data Sheet and drum label.

470 lbs. (55 gals.)  
260 lbs. (30 gals.)  
45 lbs. ( 5 gals.)